



SCHEDULE OF WINDOWS, VENTILATORS, OPENINGS	NO.	DESCRIPTION	UNIT	QTY	REMARKS
1	AM21	2100X 1350	1050	2400	aluminum sections color powder coating shutter no track with 5mm glazing
2	AM15	1500 X 1350	1050	2400	aluminum sections color powder coating shutter no track with 5mm glazing
3	AM15a	1500 X 1500	900	2400	aluminum sections color powder coating shutter no track with 5mm glazing
4	AM115	1500 X 2100	900	2400	aluminum sections color powder coating shutter no track with 5mm glazing
5	RS15	1500 X 1500	900	2400	aluminum sections color powder coating shutter no track with 5mm glazing
6	RS9	900 X 1500	900	2400	aluminum sections color powder coating shutter no track with 5mm glazing
7	RS21	2100 X 1500	900	2400	aluminum sections color powder coating shutter no track with 5mm glazing
8	SD	750 X 2100	00	2100	35 mm thick clear shutter, both side connected wood feeding single leaf with lock wood frame
9	WD	750 X 1800	00	1800	35 mm thick clear shutter, both side connected wood feeding single leaf with lock wood frame
10	MO6	600 X 1950	450	2400	aluminum sections color powder coating shutter no track with 5mm glazing
11	AL015	1500X2400	00	2400	aluminum sections color powder coating shutter no track with 5mm glazing
12	RS36	800X2100	00	2100	aluminum sections color powder coating shutter no track with 5mm glazing
13	RS48	BEAM SOFFIT	00	beam soffit	aluminum sections color powder coating shutter no track with 5mm glazing

SCHEDULE OF WINDOWS, VENTILATORS, OPENINGS	NO.	DESCRIPTION	UNIT	QTY	REMARKS
1	AV21	2100 X 750	2400	BEAM SOFFIT	aluminum sections color powder coating shutter no track with 5mm glazing
2	AV15	1500 X 750	2400	BEAM SOFFIT	aluminum sections color powder coating shutter no track with 5mm glazing
3	AV9	900 X 800	1800	2400	aluminum sections color powder coating shutter no track with 5mm glazing
4	AV6	600X800	2400	BEAM SOFFIT	aluminum sections color powder coating shutter no track with 5mm glazing
5	RA1	1200 X 1500	900	2400	R C C JALLI
6	RA9	900 X 600	1800	2400	R C C JALLI

GENERAL NOTES

1. ALL DIMENSIONS ARE IN MM.
2. REFER REMARKED DIMS WHERE EVER MENTIONED.
3. ANY DISCREPANCY IN SITE TO BE BROUGHT TO THE NOTICE OF THE ARCHITECT.
4. DRAWINGS NOT TO BE SCALED & WRITTEN DIMENSIONS HAS TO BE FOLLOWED STRICTLY.
5. DETAILS INDICATED IN ENLARGED/DIMENED DIMS SHALL SUPERSEDE THE GENERAL DRAWINGS IN CASE OF DISCREPANCY OR VARIATIONS.
6. OPENING SHALL BE LEFT FOR EXHAUST FAN IN ALL W/S.
7. TO BE REFIN IN CONSULTATION WITH AS-SERIES.
8. LOCATION OF SINK SHOWN IN L&S IS TENTATIVE.
9. ALL TOILETS TO BE SUNKEN BY 75MM.
10. ALL DOORWAYS TO BE SUNKEN BY 50MM.
11. ALL DOORWAYS IN FIRST, SECOND FLOOR TO BE SUNKEN BY 150MM.
12. ALL DOORS EXCEPT DOORS IN AM/UPS/INTEGRATED/TOILET DOOR/STORE ROOM AND LEFT LOBBY SHALL BE WITH VISION PANEL OF SIZE 150x 600 AS SPECIFIED.
13. DOORS OF AM/UPS SHALL BE WITH AIR TRANSFER GRILL OF 150x150mm.
14. DOORS OF STORE ROOM SHALL BE COVERED WITH LAMINATED SHEET INTERNALLY TO THE FULL HEIGHT AS SPECIFIED.
15. ALUMINUM WINDOWS AND VENTILATORS SHALL BE SPECIFIED AS PROVIDED WITH ALUMINUM SLAB FRAME AS SPECIFIED.
16. GLAZING IN ALL FLOORS SHALL HAVE GRILLS AS SPECIFIED.
17. GLAZING IN VENTILATORS OF TOILETS SHALL BE FORMED / PAN HEAVY GLASS.